



DOTRIX™ *Dot Matrix Cover ...* *...means beautifully clean installations!*

DOTRIX™ Dot Matrix covers and patterns are custom fit to conform to problem areas. Using our exclusive **DOTRIX™** material you can cut and fit beautiful Dot Matrix covers that match up perfectly with our window film patterns. You'll save time with less heat shrinking. A beautiful, seamless and blacked-out dot matrix area will give you the perfect installation every time.

Application is simple and easy. Unlike window films, the pressure-sensitive backing allows for easy installation without heat shrinking. The results are truly awesome!

DIRECTIONS FOR DOTRIX™ INSTALLATION

Step 1: Install Window Film First

Cut, heat form and install the window film to the rear window
(For best results, do not allow film to enter in the dot matrix or frit line area.)

Step 2: Seal the Top Edge

Be sure to **SEAL** the top edge of film just below Dot Matrix or Frit Lines with a Hard Card and paper towel. This will keep water from getting under film when applying the **DOTRIX™** pattern. Clean dot matrix area to be covered with soapy water and a yellow turbo squeegee.
(Use 3oz. Of Film-On or 1oz.soap in 32oz. Bottle)

Step 3: Spray as you Peel

Thoroughly spray the dot matrix area to be covered with the soapy solution. Peel your pattern from table or glass stand spraying vigorously with the soapy solution.

Step 4: Apply

Apply the **DOTRIX™** pattern to area of window to be covered, align with your hand and smooth out so that no light is showing. The soapy solution will allow you to slide the pattern into position, making sure you have approx. 1/8" overlap onto the tinted portion of the window. Squeegee with **yellow** turbo squeegee.
That's it!

Seal Top Edge



Spray as you Peel



Apply DOTRIX™

